



Useful Options:

- Electrical Drive
- Pasteuriser
- Hot water-fired heater
- Pump function
- Remote control
- Electrical Heater
- Churn support frame
- Colostrum churn
- Drenching probe

Technical Specifications*

Power Supply	230V / 16A or 400V / 16A
Pump Capacity	approx. 40 l/min
Heating Power	3kW, 5kW or 6kW

	Tank Capacity	Width (cm)	Length (cm)	Height (cm)
Milktaxi 100 l	115 l	60	126	109
Milktaxi 150 l	180 l	75	129	109
Milktaxi 260 l	290 l	76	133	119
Milktaxi Trailer	290 l	120	140	125

* Technical specifications subject to change!

Holm & Laue GmbH & Co. KG
Moorweg 6
24784 Westerrönfeld, Germany

Phone: +49 (0)4331 20 174-0
Fax: +49 (0)4331 20 174-29
E-mail: info@holm-laue.de
Web: www.holm-laue.de



MilkTaxi 3.0

The best just got better



Intuitive, simple operation

The information given on the display makes operation almost self-explanatory. This means minimal training is required for you and your staff. Many functions can be programmed on a timer.



Remote control

Using the remote control on the dispensing arm, you can conveniently feed calves up to even 10m away from the Milktaxi, without any cables.



Dark? Not a problem

Thanks to the integrated LED headlight you can always see where you are driving. This ensures that feeding your calves at night is no longer a problem, even in remote calf hutches.



Sturdy 4-wheel chassis

The Milktaxi is extremely sturdy with its low-fulcrum, 4-wheel design. Even when travelling at speed and fully laden, it does not tip over.



All-terrain

With its 40cm front wheels and raised ground clearance, any bumps in the ground or low thresholds pose no obstacle.



EL-AN electrical drive

All models come with the electrical drive offering stepless adjustment between two forwards and reverse speeds. This not only makes feeding fun, but also protects your back.



CHILD'S PLAY
EFFICIENT FEEDING
SAFE FEEDING

Simple dosing

Thanks to 9 freely programmable dosing levels, you can dose almost any quantity of feed – without annoying drips. What is more, the handle is ergonomically designed and very lightweight.



Powerful floor-mounted agitator

Each milk replacer is dissolved in seconds. Its floor mounting offers maximum operational stability and does not get in the way when cleaning the tank.



Gentle heating

The unique heating foils warm the milk gently without burning and sticking to the tank. Even high heating capacities of 6 kW can easily be achieved.



Even more volume

You can choose the right Milktaxi for you from our range of four different models: 100, 150, 260 and 260 l as a trailer.



Pasteuriser

Dangerous pathogens are killed at 63 °C for 35 minutes. All start times can be programmed to suit your requirements. This means that you can programme your milk to be fully pasteurised by the time you get to the barn in the morning.



Automatic cooling function

The automatic cooling function is particularly practical for use with robotic milkers. This keeps the milk fresh and your calves healthy!



Automatic cleaning

You can clean the tank easily through the opening lid. The automatic cleaning programme ensures optimum hygiene. Residue from the pump and hose can be discharged fully.

